

Component - Plastics

E194157

[\[guide info\]](#)**COSSA POLIMERI SRL**

VIA DEI BRUGHIROLI 6, GORLA MAGGIORE VA 21050 IT

**ESTAPROP 1040 T8 V0**

Polypropylene (PP), furnished as pellets

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
NC, BK	1.5	V-0	-	-	65	65	65
Comparative Tracking Index (CTI): -		Inclined Plane Tracking (IPT): -					
Dielectric Strength (kV/mm): -		Volume Resistivity (10 <sup>x</sup> ohm-cm): -					
High-Voltage Arc Tracking Rate (HVTR): -		High Volt, Low Current Arc Resis (D495): -					
Dimensional Stability (%): -							

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents.

ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1999-03-22

Last Revised: 2003-10-24

© 2017 UL LLC

**IEC and ISO Test Methods**

Test Name	Test Method	Units	Thk (mm)	Value
Flammability	IEC 60695-11-10	Class (color)	1.5	V-0 (NC, BK)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	°C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	°C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	°C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	°C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m <sup>2</sup>	-	-
ISO Izod Impact	ISO 180	kJ/m <sup>2</sup>	-	-
ISO Charpy Impact	ISO 179-2	kJ/m <sup>2</sup>	-	-